

## Les Atouts

**Clear grinding visor**  
**Particules filtration (PRSL)**  
**2 airflows**  
**Clogged-filter alarm**  
**Low-battery alarm**  
**Storage bag**

## Navitek Clear Visor Airkos



## La technique

Material	Polyamide	Spark protection	Indirect filter cover
Standards	EN12941	Hose cover	Included - Flame retardant
Warranty	1 year on battery and motor	Sound level	60dB
Outside protection	Clear polycarbonate	Headgear	Confort - 4 settings
Filtration	TH2PSL	Airflow	180l/m and 220l/m
Sound alarm	Clogged filter	Operating time	9-10 hours
Battery	Lithium-Ion - Removable	Sound alarm	Low battery charge
Charger	6 hours smart charge (for CR7020)	Belt adjustment	Double fast setting - No velcro
Belt	Large and padded Neoprene	Weight	1180g (unité+batterie+ceinture+filtre)



Visor polycarbonate (x5)	AX 3415
Sweatband (x2)	AX 1140
Headgear with airduct	CR 7025
Large padded belt	CR 7001
Optional confort harness	CR 7002
Belt extension	CR 7003
Air hose with connections	CR 7010
Flame retardant hose cover	CR 7012
Standard Lithium-ion battery	CR 7020
Heavy-duty Lithium-ion battery	CR 7021
Lithium-ion battery european charger	CR 7022
Lithium-ion battery international charger	CR 7023
Navitek* flame retardant face seal	CR 7032
PRSL main filter	CR 7050
Pre-filter (x10)	CR 7060
Pre-filtre with active carbons (x10)	CR 7070
Storage bag	CR 7090

The Navitek® Clear Visor offers one of the largest clear grinding visors available on the market. The Navitek® shell and all its polycarbonates are certified for grinding with the specific standards EN 166B and EN 175B. The visor is made in perfectly clear 1,0mm thick polycarbonate.

The excellent ergonomics provides perfect protection of the forehead, the ears and the neck. The Navitek® Clear Visor is equipped with the longitudinal headgear with 4 settings: height, width, angle, and longitudinal adjustment for welders operating with corrective glasses.

When associated to the Airkos®, the Navitek® Clear Visor provides the filtration of Solid and Liquid Particules (PSL). The bolted and flame retardant face seal guarantees a limited TH2 inward leakage inside the headtop. The main filter on the Airkos® is classified as « Re-usable » (PRSL), and does not need to be replaced after every shift. The visual and sound alarm will inform the operator when to replace the filter.

The PRSL filter of the Airkos® is equipped with a pre-filter, blocking the largest particules and extending the lifecycle of the main filter. As an option, a pre-filter with active charcoals is available.

The Airkos® blower unit (PAPR) is approved and certified according to the EN 12941 standard, with and only with the Navitek® headtop. Cf certificate below :



Completing the alarm for the clogged filter, the filtration unit is also equipped with a distinctive alarm for the battery, informing the operator when the charge is running low.

The Airkos® is delivered with a standard 4-cell Lithium-ion battery. A heavy-duty battery with 6 Lithium-ion cells is also available. When equipped with the standard battery (CR7020), the Airkos® can provide up to 10 hours of operating time (with a new filter and on minimum airflow). Once equipped with the heavy-duty battery (CR7021), the Airkos® offers up to 15 hours, under the same conditions.

According to the close environment and the operator's habits, it is possible to select between 2 airflows on the Airkos®. 180l/m is the minimum airflow. With a simple push on the control knob, the unit increases the airflow to 220l/m.

A very large and padded belt provides an excellent comfort and a perfect support of the blower unit. As options, a padded harness and/or a belt extension are available to complete the existing belt.



Each Navitek® Clear Visor Airkos is delivered with its own storage bag. The Airkos® storage bag is perfect for transport and stock of buffer spare parts.